

## SPRING OFFER!

### Unibody Gas Ball Valve with double "O" Ring

Certified CSA in USA and Canada according to ANSI Z21.15-1997, ANSI Z21.15a-2001, AGA Requirement No. 3-88, CGA Requirement CR91-002, ASME B16.44-2002 & UL according to Subject 258.

Pressure rating  
125 WSP – 400 WOG  
Temperature Rating max. 300 °F water  
(depending on pressure and size)

Forged Brass Body  
Standard Port Opening  
Threaded Ends according to NTP (ANSI Standard)  
Chrome Plated Solid Ball



Fig. 496 FB  
Female / Flare Ends

Available in:

- Fig. 496 FF Unibody, Female Ends
- Fig. 496 FB Unibody, Female/Flare Ends
- Fig. 496 BB Two Piece Design, Flare Ends

Size	Available quantity	Special price € per piece
3/8" female ends	1024	1,42
1/2" female ends	5436	1,55
3/8" flare x 1/2" female	984	1,80
1/2" flare x 1/2" female	1541	1,80
3/8" Flare ends	1567	1,91
1/2" Flare ends	987	1,91



Buy the total quantity and have a nice holiday with our wonderful electric refrigerator for car you will get

**FOR FREE!**

Don't lose time: this offer is only valid thru May 31 2010 !